ELLIPTICAL, OVAL AND ROUND OPENING PORTS (H-TRIM)

• C C Approved. According to ISO / DIS 12216 LE, LO & LR type are supplied to Area III, III. Designs for craft type "any".


- 316 stainless steel machined rolled ports. 316 stainless steel machine stamped frames. Hand Polished and electro polished to provide long lasting protection against corrosion.
- Weather resistant themo-plastic Sanplane gasket.
- High Strength tempered glass.
- Optional fiberglass screens with rubber gaskets to ensure a tight fit on the opening port.



MODEL No.	A x B	C x D	E x F	GLASS
	MODEL	CUT OUT	OVERALL	THICKESS
LE-0718	7 X 17 ³ ⁄4	7 ³ ⁄ ₈ x 18	9 ⁵ / ₈ x 20 ³ / ₈	⁵ /16
	178×451	187×458	244×518	8



MODEL No.	A x B MODEL	C x D CUT OUT	E x F OVERALL	GLASS THICKESS
LO-0512	5 X 12 127×305	5 ⁵ ⁄ ₈ X 12 ⁵ ⁄ ₈ 143×321	7 ⁷ ⁄ ₈ X 14 ⁷ ⁄ ₈ 200×378	5/16 8
LO-0614	6 X 14 153×356	6 % X14 %	8 ⁷ ⁄ ₈ X 16 ⁷ ⁄ ₈ 225×429	5/16 8
LO-0714	7 X 14	7 ⁵ ⁄ ₈ X14 ⁵ ⁄ ₈	9 % X 16 %	5/16 8
LO-0716	7 X 16 178×406	7 ⁵ ⁄ ₈ X16 ⁵ ⁄ ₈ 194×422	9 % X 18 8 251×479	8 5/16 8
LO-0718	7 X 18 178×457	7 ⁵ ⁄ ₈ X18 ⁵ ⁄ ₈ 194×473	9 % X 20 8 251×530	5/16 8
LO-0816	8 X 16 203×406	8 5% X165% 219×422	10 ⁷ ⁄ ₈ X 18 ⁷ ⁄ ₈ 276×479	5/16 8
LO-0818	8 X 18 203×457	8 % X18 % 219×473m	10 ⁷ / ₈ X 20 ⁷ / ₈ 276×530	5/16 8



- "G" available $1\frac{1}{4}\frac{3}{32\text{mm}} \cdot 1\frac{1}{2}\frac{3}{38\text{mm}} \cdot 2\frac{1}{2}\frac{3}{63\text{mm}} \cdot 3\frac{7}{76\text{mm}} \cdot 3\frac{1}{2}\frac{3}{88\text{mm}}$
- 2.Special spigot size "G" available from 1^{"25mm} ~5^{"125mm}
- 3. The spigot height are needed, while ordering.



MODEL No.	A	C	F	GLASS
	MODEL	CUT OUT	OVERALL	THICKESS
LR-0500	5	5 ⁵ / ₈	7 ⁷ / ₈	5/16
	127mm	143	200	8
LR-0600	6	6 ⁵ / ₈	8 ⁷ / ₈	5/16
	153mm	168	225	8
LR-0700	7	7 ⁵ ⁄8	9 ⁷ / ₈	5/16
	178mm	194	251	8
LR-0800	8	8 ⁵ / ₈	10 ⁷ / ₈	5/16
	203mm	219	276	8







